

C € 0085

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085DL0067

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	InterApp-Valcom S.A. Calderon de la Barca, 12, E-28860 Paracuellos de Jarama (Madrid)
Distributor <i>Vertreiber</i>	InterApp-Valcom S.A. Calderon de la Barca, 12, E-28860 Paracuellos de Jarama (Madrid)
Product Category <i>Produktart</i>	gas fittings: Shut-off valve, magnetic/ motor/ pneumatic operated (4307)
Product Description <i>Produktbezeichnung</i>	pneumatic operated automatic shut-off valve
Model <i>Modell</i>	Desponia, Desponia plus
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
Test Reports <i>Prüfberichte</i>	type testing: 19-00310-177 from 30.12.2019 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 161 (01.04.2013)

Date of Expiry / File No. 31.03.2030 / 20-0169-GEE
Ablaufdatum / AZ

31.03.2020 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
Desponia, Desponia plus	nominal diameter: DN 50 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 65 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 80 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 100 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 125 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 150 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 200 max. operating pressure: 5 bar	
Desponia, Desponia plus	nominal diameter: DN 250 max. operating pressure: 5 bar	

Hints of Utilization /Remarks
Verwendungshinweise / Bemerkungen

valve class: A

ambient temperature range: -20...+60 °C

connection: ends for clamping-connection for the installation between flanges according to DIN EN 1092

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.